L Number	Hits	Search Text	DB	Time stamp
-	50	("4625310"	USPAT;	2003/12/18 09:40
		"5690575"	US-PGPUB;	
		"5293079"	EPO; JPO;	
		"4348759"	IBM_TDB	
		"4507576"		
		"4800294"		l
		"5192881"	•]
		"5304923" "5336944"]	,
		"5336944"		1
		, , , , , , , , , , , , , ,		1
		"5530370" "5604750" "5682352" "5844913"		İ
		"5682352"		1
		"5844913"		
1		"5951705"		
		"5999013"		
		"6194910" / O / Vare \$	1	1
		"6202186"	\mathcal{U}	
		"6202186" "6232759"	Ţĭ	
1		"6348785" \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		1
		"4523143"		
		"5500603"		
		"5936876"		
		"6043672"		
		"6083848"		
		"4907230" "5353308"		
		"5623500"		
		RE31828		
Ì		"4504783" / "A504783"		1
1		"4608669"		
		"4782283"	İ	
		"5049814"		
		"5177440"		
		"5243274" \		
		"5258985"		İ
		"5272434"		
		"5394098"		1
		"5524114"		
		"5570034" 3 14 / \$		
		"5583786"		
		"5610826"]
		"5617531" "5621312"		.
		"5680936"		
		"5805611"		
		"5818251"		
		"5878051"	1	
		"5889936"		
		"5905381").pn.		
		-		
-	1265	(variable change\$4 flexible shifting	USPAT;	2003/12/18 10:40
		adapt\$4 alter\$4 adjust\$4 switch\$4) with	US-PGPUB;	
		(voltage adj generat\$3) and (sense adj	EPO; JPO;	
		amp\$6)	IBM_TDB	0000/10/10 10
-	110022	reference adj voltage	USPAT;	2003/12/18 09:47
			US-PGPUB;	
			EPO; JPO;	
1_	1853	(loop adj back loopback) with (generat\$3	IBM TDB USPAT;	2003/12/18 09:48
-	1853	compar\$3)	US-PGPUB;	2003/12/18 09:48
-		Comparas	EPO; JPO;	
			IBM TDB	
_	81043	DAC D/A adj convert\$3 digital-to-analog	USPAT;	2003/12/18 09:55
	01045	adj convert\$3	US-PGPUB;	-555, 12, 10 03.55
			EPO; JPO;	
	i		IBM TDB	
-	29832	compar\$4 same reference same (analog	USPAT;	2003/12/18 10:00
		direct adj current DC) same (volt\$3 power	US-PGPUB;	
		level\$3)	EPO; JPO;	
			IBM_TDB	

	2300	boundary-scan boundary adj scan	USPAT;	2003/12/18 10:02
		,	US-PGPUB;	. , , , ,
			EPO; JPO; IBM TDB	
-	1	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	USPAT;	2003/12/18 10:11
		adapt\$4 alter\$4 adjust\$4 switch\$4) with	US-PGPUB;	
		<pre>(voltage adj generat\$3) and (sense adj amp\$6)) and (reference adj voltage) and</pre>	EPO; JPO; IBM TDB	
		((loop adj back loopback) with (generat\$3	_	
	=	compar\$3)) and (DAC D/A adj convert\$3 digital-to-analog adj convert\$3) and		
		(compar\$4 same reference same (analog		
		direct adj current DC) same (volt\$3 power		
		level\$3)) and (compar\$4 same reference same (analog direct adj current DC) same		
		(volt\$3 power level\$3)) and (boundary-scan		
	1	boundary adj scan) ((variable change\$4 flexible shifting	HCDAT.	2003/12/18 10:11
_	1	adapt\$4 alter\$4 adjust\$4 switch\$4) with	USPAT; US-PGPUB;	2003/12/16 10:11
		(voltage adj generat\$3) and (sense adj	EPO; JPO;	
		<pre>amp\$6)) and (reference adj voltage) and ((loop adj back loopback) with (generat\$3</pre>	IBM_TDB	
		compar\$3)) and (DAC D/A adj convert\$3		
		digital-to-analog adj convert\$3) and (compar\$4 same reference same (analog		
	•	direct adj current DC) same (volt\$3 power		
		level\$3)) and (compar\$4 same reference		:
		<pre>same (analog direct adj current DC) same (volt\$3 power level\$3))</pre>		
-	1	((variable change\$4 flexible shifting	USPAT;	2003/12/18 10:12
		adapt\$4 alter\$4 adjust\$4 switch\$4) with (voltage adj generat\$3) and (sense adj	US-PGPUB; EPO; JPO;	
		amp\$6)) and (reference adj voltage) and	IBM_TDB	
		((loop adj back loopback) with (generat\$3	_	
		compar\$3)) and (DAC D/A adj convert\$3 digital-to-analog adj convert\$3) and		
		(compar\$4 same reference same (analog		
		<pre>direct adj current DC) same (volt\$3 power level\$3))</pre>		
-	1	((variable change\$4 flexible shifting	USPAT;	2003/12/18 10:12
		adapt\$4 alter\$4 adjust\$4 switch\$4) with (voltage adj generat\$3) and (sense adj	US-PGPUB; EPO; JPO;	
		amp\$6)) and (reference adj voltage) and	IBM_TDB	
		((loop adj back loopback) with (generat\$3		
		compar\$3)) and (DAC D/A adj convert\$3 digital-to-analog adj convert\$3)		
-	263109	(voltage adj generat\$3 source) and (sense	USPAT;	2003/12/18 10:42
		adj amp\$6 receiver comparator)	US-PGPUB; EPO; JPO;	
			IBM_TDB	
-	47441	((voltage adj generat\$3 source) and (sense adj amp\$6 receiver comparator)) and	USPAT; US-PGPUB;	2003/12/18 10:42
		(reference adj voltage) ((loop adj back	EPO; JPO;	
<u> </u>	57	loopback) with (generat\$3 compar\$3)) ((voltage adj generat\$3 source) and (sense	IBM_TDB	2003/12/10 10-50
_	57	adj amp\$6 receiver comparator)) and	USPAT; US-PGPUB;	2003/12/18 10:50
		(reference adj voltage) and ((loop adj	EPO; JPO;	
_	1352	back loopback) with (generat\$3 compar\$3)) (324/522,523,527).ccls.	IBM_TDB USPAT;	2003/12/18 10:44
	1002	,,,,,,,,,	US-PGPUB;	
			EPO; JPO; IBM TDB	
-	2360	(714/819,727,736,734,733).ccls.	USPAT;	2003/12/18 10:45
			US-PGPUB;	
			EPO; JPO; IBM TDB	
-	518	(341/94).ccls.	USPĀT;	2003/12/18 10:45
			US-PGPUB; EPO; JPO;	
			IBM TDB	

	1 0	(((voltage adj generat\$3 source) and	USPAT;	2003/12/18 10:46	1
		(sense adj amp\$6 receiver comparator)) and	US-PGPUB;	2003/12/10 10:40	
		(reference adj voltage) and ((loop adj	EPO; JPO;		
		back loopback) with (generat\$3 compar\$3)))	IBM TDB		ŀ
		and ((324/522,523,527).ccls.) and	1207-122	ì	
		((714/819,727,736,734,733).ccls.) and			
		((341/94).ccls.)			
_	0		USPAT;	2003/12/18 10:46	
		(sense adj amp\$6 receiver comparator)) and	US-PGPUB;	2000, 22, 20 20, 10	
		(reference adj voltage) and ((loop adj	EPO; JPO;	İ	
		back loopback) with (generat\$3 compar\$3)))	IBM TDB		
		and ((324/522,523,527).ccls.)	3313_333		
_	72		USPAT;	2003/12/18 10:48	
		back loopback) with (generat\$3 compar\$3))	US-PGPUB;		
		, , , , , , , , , , , , , , , , , , ,	EPO; JPO;		
			IBM TDB		
_	7484	((reference adj voltage) and ((loop adj	USPĀT;	2003/12/18 10:48	ŀ
		back loopback) with (generat\$3 compar\$3)))	US-PGPUB;		l
		and ((324/522,523,527).ccls.) and	EPO; JPO;		١
		((714/819,727,736,734,733).ccls.) nad	IBM TDB		١
		((341/94).ccls.)	_		l
_	0	((reference adj voltage) and ((loop adj	USPAT;	2003/12/18 10:49	l
		back loopback) with (generat\$3 compar\$3)))	US-PGPUB;		l
		and ((324/522,523,527).ccls.) and	EPO; JPO;		l
		((714/819,727,736,734,733).ccls.) and	IBM TDB		l
		((341/94).ccls.)	_		l
_	1	(((voltage adj generat\$3 source) and	USPAT;	2003/12/18 10:49	
		(sense adj amp\$6 receiver comparator)) and	US-PGPUB;		
		(reference adj voltage) ((loop adj back	EPO; JPO;		
		loopback) with (generat\$3 compar\$3))) and	IBM_TDB		
		((324/522,523,527).ccls.) and	_		
		((714/819,727,736,734,733).ccls.)			
_	1		USPAT	2003/12/18 11:11	
-	1		USPAT	2003/12/18 11:12	
-	1		USPAT	2003/12/18 11:12	
-	1		USPAT	2003/12/18 11:26	
_	1		USPAT	2003/12/18 11:32	1



Advanced Search

<u>Preferences</u>

Language Tools

Search Tips

DAC loop reference voltage regis

Google Search ⊕

Web - Images - Groups - Directory - News -

Searched the web for DAC loop reference voltage register switch. Results 1 - 50 of about 5,840. Search took (

Chipdir - Chips by category

... pll, Phase Locked Loop. port, Port, buffer, driver, ff, latch, receive, xmit, xcvr. ... video, Video, adc, audio, crt, dac, shift, tv. ... vref, Voltage reference, volt. ... www.xs4all.nl/~ganswijk/chipdir/f/ - 33k - Cached - Similar pages

Sponsored Links

Voltage Reference ICs Huge selection of low cost, high accuracy, small, low power refs! www.maxim-ic.com

Interest:

See your message here...

<u>LeCroy Research Systems Model MHV100 HV Controller</u>

... Built-in Band Gap **Voltage Reference**; Feedback Error Amp for **Voltage** Control **Loop**;

1.6 MHz ... Two uncommitted op-amps and auxiliary **DAC** (8 bit) output and ADC ... www.lecroy.com/lrs/dsheets/mhv100.htm - 5k - Cached - Similar pages

[PDF] Dual Current-Output Parallel-Input, 16-/14-Bit DAC Preliminary ...

File Format: PDF/Adobe Acrobat - View as HTML

... tests are performed in a closed **loop** system using ... R 2R Figure 5. Equivalent R-2R **DAC** Circuit Note ... The **reference voltage** inputs exhibit a constant nominal input ... www.analog.com/UploadedFiles/Data_Sheets/ 43093437AD5547_57_prc.pdf - <u>Similar pages</u>

[PDF] EVAL-AD5379 Preliminary Technical Data

File Format: PDF/Adobe Acrobat - View as HTML

... in the system to avoid ground **loop** problems ... AD5379 40-Channel **DAC** Parallel Interface 28 pin Header ... Serial Interface 36 pin Connector 3V **Reference** VREF (-) Gain ... www.analog.com/UploadedFiles/Evaluation_Boards/ Tools/25442813AD5379EB_prc.pdf - <u>Similar pages</u>

[More results from www.analog.com]

[PDF] MAX555 300Msps, 12-Bit DAC with Complementary Voltage Outputs

File Format: PDF/Adobe Acrobat - View as HTML

... VIN) 0V to +1.25V Reference Input Current ... MAX555

300Msps, 12-Bit **DAC** with Complementary **Voltage** ... 3 20 AV OL Open-**Loop** Gain MHz ...

www.gaw.ru/doc/Maxim/1127.PDF - Similar pages

IPDFI A Universal Micro-Sensor Interface Chip with Network ...

File Format: PDF/Adobe Acrobat - View as HTML

... Gain Amp: self-test input 6b **DAC** Capacitive Amp ... capacitive readout circuit; with a 3pF **reference** capacitor and ... the input of a closed-**loop** differential amplifier ... www.egr.msu.edu/~mason/pubs/umsi mwscas2002.pdf - Similar pages

IPDFI XRD5412

File Format: PDF/Adobe Acrobat - View as HTML

... 85 °C BLOCK DIAGRAM Figure 1. Block Diagram Shift Register - + V REFIN V ... Output 5 AGND Analog Ground 6 V REFIN Voltage Reference Input 7 V OUT DAC Output 8 ...

www.exar.com/products/xrd5412.pdf - Similar pages

[PDF] XRD5408/10/12

File Format: PDF/Adobe Acrobat - View as HTML

... is constrained by the output swing of the fixed +2 closed-loop gain amplifier. ... The reference voltage must be positive because the XRD5408/10/12 DAC is non ... www.exar.com/products/xrd5408.pdf - Similar pages

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Welcome United States Patent and Trademark Office Help FAQ Terms IEEE Peer Review Quick Links Welcome to IEEE Xplore Your search matched 1 of 989552 documents. A maximum of 1 results are displayed, 15 to a page, sorted by Relevance in descending order. You may refine your search by editing the current search expression or entering a new one the text box
Welcome to IEEE Xplores Your search matched 1 of 989552 documents. A maximum of 1 results are displayed, 15 to a page, sorted by Relevance in descending order.
Your search matched 1 of 989552 documents. A maximum of 1 results are displayed, 15 to a page, sorted by Relevance in descending order.
Tables of Contents You may refine your search by editing the current search expression or entering a new one the text box Then click Search Again. ((dac)and (reference voltage)) and(amp) Search Again
O- Journals & Magazines Results: Journal or Magazine = JNL Conference = CNF Standard = STD
Conference Proceedings Standards 1 A ratio insensitive cyclic D/A conversion technique Wong, K.C.; Burra, G.; Chao, K.S.; Circuits and Systems, 1991., Proceedings of the 34th Midwest Symposium on May 1991 Page(s): 723 -726 vol.2
Member Services [Abstract] [PDF Full-Text (216 KB)] IEEE CNF
O- Join IEEE O- Establish IEEE Web Account
O- Access the IEEE Member Digital Library

<u>Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account | New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting No Robots Please | Release Notes | IEEE Online Publications | Help | FAQ | Terms | Back to Top</u>

Copyright © 2003 IEEE — All rights reserved